



Special Products

Product information

MR® 750 Ultrasonic Coupling Agent



PRODUCT DESCRIPTION

- For ultrasonic testing in non-destructive testing of materials
- Water based
- Acoustically exact
- Optimal conducting capacity
- High viscosity, not dripping
- With corrosion inhibitor
- Free of fat, silicone and formaldehyde
- Water washable
- Odourless
- Not toxic
- Well tolerated by skin
- Contact with skin and clothes: indifferent; pH-value approx. 8,0
- No declaration of hazardous ingredients – ECO-LINE

APPLICATION

- Apply MR® 750 Ultrasonic Coupling Agent on the surface of materials. Bring probe into contact with the surface and begin testing. MR® 750 Ultrasonic Coupling Agent will disperse evenly under the probe.
- MR® 750 Ultrasonic Coupling Agent may be used for coated materials, plastics, rubber/metal-compounds, etc.
- After testing remove MR® 750 Ultrasonic Coupling Agent from the surface with a dry cloth, with water or with MR® 88 Remover.

FURTHER INFORMATION

You will receive the bucket with a not punched lid. If required, please order the dispenser with a punched lid.
Art.-no.: G87 L
(see photograph)

MR® 750 ULTRASONIC COUPLING AGENT



Art.-No. G87 L

APPROVALS/SPECIFICATIONS

EN ISO 25493



Determination of chlorine-, fluorine- and sulphur-contents in accordance with ASME Code V, Art. 5, T-533 and ASME Code V, Art. 6, T-641

DELIVERY FORM

- 250 ml
- 5 L
- 30 L

MINMUM SHELF LIFE

- 1 year, stored at storage temperature

TEMPERATURES

- Storage: +5 - +45°C
- Usage: -10 - +80°C