

**MR<sup>®</sup> 67 Penetrant red and fluorescent**



### Product Characteristics

- Water and solvent removable penetrant red and fluorescent
- Penetrant Typ II and Typ III
- Sensitivity level 2 acc. EN ISO3452:2
- Crack indication colour „red and fluorescent“
- Suitable for all metals (suitability for plastics and ceramics to be checked before application)
- Carrier medium water

### Minimum shelf life / Temperatures

Aerosol / Bulk:  
3 years at storage temperature  
Storage: + 5 °C - + 45 °C  
Application: + 5 °C - + 100 °C



### Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-5
- ASTM D516
- ASTM E165
- RCC-M
- ASTM E1417
- ASME Code V, Art. 6




### Further Information

Process description according to EN ISO 3452-1 on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en). For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

### Suggested Products

Pre-cleaner: MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, MR<sup>®</sup> 3001, MR<sup>®</sup> 3002  
Remover: MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, Water  
Developer: MR<sup>®</sup> 70, MR<sup>®</sup> 703 W (+5 °C)  
Testblock: Reference-Testblock 1 and 2, ASTM Testblock

### Delivery Form



\*\*technical changes reserved!\*\*