

MR[®] 68 NF Penetrant red and fluorescent



Product Characteristics

- Water and solvent removable penetrant red and fluorescent
- Penetrant Typ II and Typ III
- Sensitivity level 2 acc. EN ISO3452:2
- Crack indication colour „red and fluorescent“
- Suitable for all metals (suitability for plastics and ceramics must be checked before use)
- Carrier medium Glycol

Minimum shelf life / Temperatures

Aerosol / Bulk:
3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: - 10 °C - + 50 °C



Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- ASME Code V, Art. 6
- RCC-M
- PMUC
- TLV 9017
- 01:2011-01



Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR[®] 79, MR[®] 85, MR[®] 88, MR[®] 3001, MR[®] 3002
Remover: MR[®] 79, MR[®] 85, MR[®] 88, Wasser
Developer: MR[®] 70, MR[®] 703 W (+5 °C)
Test block: Reference-Testblock 1 and 2, ASTM Testblock

Delivery Form



technical changes reserved!